



ADVANCED LOW HUMIDITY PERFORMANCE

LGR 7000XLi

THERE'S NO DEHUMIDIFIER IN THE UK LIKE IT. *PERIOD.*

Breaking the performance barriers as the new category leader, the LGR 7000XLi removes more water than any other dehumidifier in its category!

To achieve the 7000's amazing performance, Dri-Eaz engineers developed the Advanced Crossflow Technology to **maximise energy utilisation**. At the same time, the unit's built-in sensors constantly monitor real time performance data to automatically calculate ideal operating parameters.

With its outstanding performance at AHAM and saturation, plus **40% better low-grain performance than competitive units**, the 7000XLi is truly the top performer.

The LGR 7000XLi control panel **displays inlet and outlet temp and RH in real time**. Plain

English text (and three other languages) provides clear operational information.

The unit's design also **greatly simplifies cleaning and maintenance**. Simply remove four bolts and the cover easily lifts off to fully expose the coils and the heat exchange block for easy cleaning.

The 7000XLi also includes a **built-in humidistat** for set-and-forget humidity level control.



- » **ADVANCED CROSSFLOW TECHNOLOGY** maximises efficiency even in low humidity environments. Ensures best performance across range.
- » **SELF-MONITORING SYSTEM.** Built-in sensors monitor performance parameters allowing for automatic fan speed adjustments.
- » **BUILT-IN HUMIDISTAT** and plain-language control panel messages



- » **SEALED LARGE-CAPACITY PUMP BASIN** - large enough to handle the water from an unintentional defrost after a power outage or other unexpected shut-down.
- » **ERGONOMIC DESIGN.** Taller handle for easier use on stairs, folds down for storage. Integrated cord and hose storage.
- » **VERSATILE APPLICATION** - standard 30.5 cm. ductable outlet.
- » **LEGENDARY ROTOMOULDED HOUSING** - practically indestructible - resists dents and dings - stackable for storage - saves room in warehouse.



- » **BEST PERFORMER**
- » **SMART CONTROLS** AUTOMATICALLY ADJUSTS
- » **TRUE TESTED LGR**
- » **LOW RUNNING COSTS** ONLY USES 4 AMPS



MODEL	F412-230V
POWER	4.0 AMPS, 230V
WATER REMOVAL MAX (32.2°C/90%RH)	91 LITRES / DAY
WATER REMOVAL (26.7°C/80%RH)	58 LITRES / DAY
PROCESS AIR (MAX.)	513 CMH, FLOOR-LEVEL OUTLET
DIMENSIONS	85 x 51 x 51 CM
USE WEIGHT	49 KG
DRAIN HOSE	12.2 M
POWER CORD	7.6 M
SAFETY	CE
CONSTRUCTION	Rotomoulded shell.

- » **RUGGED BUILD**
- » **EASY CLEANING**
- » **OPERATES DOWN TO 20% RH**

For **professional, reliable, robust** restorative drying equipment and the support you deserve...

CALL 01908 611211



WWW.DRI-EAZ.CO.UK

22 PLOVER CLOSE, INTERCHANGE PARK | NEWPORT PAGNELL. MK16 9PS

