

ROOFTEC® XCS 500

SO MUCH MORE THAN

JUST A PRESSURE WASHER!



ALL-IN-ONE Soft Washing AND Pressure Washing to Clean:

- Concrete Roof Tiles
- Block Paving
- Composite Decking
- Vinyl Siding
- Concrete

- Wood Decks
- Clay Tiles
- UPVC
- Asphalt Drive Ways
- Stone Masonry

AND virtually any other exterior substrate!

HIGH PRESSURE CLEANING

- Set up to 2500 PSI for concrete cleaning
- · Set up to 1000 PSI for wood cleaning
- Able to use standard pressure washing tips, oscillating tip, or up to a 50mm surface cleaner
- Use metering valves on machine to pre-treat and post-treat with cleaning solutions

LOW PRESSURE CLEANING

- Set to below 600 PSI for more delicate substrates (roofing, siding, etc.)
- Mix manifold injects both surfactants and high strength Sodium Hypochlorite
- Uses food-grade, stainless steel Suttner spray gun with i-rod
- Spray up to 10 to 12 Metres for easy roof and siding cleaning from the ground

FEATURES

- 21 litre/Minute, High Performance General Pump with Stainless steel heads and ceramic plungers for chemical injection
- Extremely reliable and quiet 14hp Kohler Engine able to run for 7 hours on a single tank of fuel
- Adjust between 100 and 2500 psi quickly with a pressure regulator
- Adjust SH easily between 0 and 6% and meter surfactant flow from 0 to 38 Litres/Minute

SPECIFICATIONS

ENGINE SPEED
WATER PUMP RPM
WATER PUMP FLOW RATE
BLEACH TANK CAPACITY
UTILITY TANKS CAPACITY
CONSOLE WEIGHT
MAX OPERATING WEIGHT
DIMENSIONS (H×D×W)
INCLUDED SOLUTION HOSE

INCLUDED SUPPLY HOSE INCLUDED ACCESSORIES

2500 RPM (MAX) / 900 RPM (IDLE)
1785 RPM (MAX)
21 LITRE/MINUTE (MAX)
415 LITRES
45 LITRES (EACH)
291 Kg (DRY)
835 Kg (FULL TANKS)
104.14 X 149.86 X 121.92 CM
60 METRES HIGH PRESSURE/CHEM
RESISTANT HOSE
30 METRES STANDARD 12mm GARDEN HOSE

STAINLESS STEEL SPRAY GUN, J-ROD W/4 TIPS

LEGEND BRANDS EUROPE

LEGEND BRANDS EUROPE | 22 PLOVER CLOSE INTERCHANGE PARK, NEWPORT PAGNELL MK16 9PS, UK | +44 (0)1908 611 211 | LegendBrandsEurope.com